

SECTION I

GENERAL INFORMATION

Distributor's Name and Address:
PerfectData Corporation
110 West Easy Street
Simi Valley, California 93065-1689
(805) 581-4000

PRODUCT NAME: STATCLEAN
105542-1
106173-1
106197-1
106197-2
106284-1
106287-1
106305-1

HMIS Rating
Health 1
Flammability 2
Reactivity 0
Personal Protection A

EMERGENCY CONTACT: CHEMTREC (800) 424-9300

SECTION II

HAZARDOUS COMPONENTS

MATERIAL(S)	CAS #	ACGIH TLV	OSHA PEL	APPROX%	OTHER INFO/ VAPOR PRESSURE
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm	*3	37.0 mmg Hg @ 20°C.
Polysolve EB	111-76-2	25 ppm	50 ppm	*4.5	0.88 mg Hg @ 25°C.
Aqua Ammonia, 26°Be	7664-44-7	25 ppm		*0.1	8.5 atm @ 20°C.
A-46				5	46 psig @ 70°F.
Isobutane (80%)	75-28-5	800 ppm			
Propane (20%)	74-98-6	1000 ppm			

* = Less than

SECTION III

PHYSICAL DATA

BOILING RANGE (Concentrate): Above 100°F.

EVAPORATION RATE (Concentrate): Slower than Ethyl Ether

VAPOR DENSITY (Concentrate): Heavier than Air

ODOR: Floral bouquet

APPEARANCE: White, Foamy

PERCENT VOLATILE BY WEIGHT (Aerosol): 12% VOC

WEIGHT PER GALLON (Concentrate): 8.25#/Gal.

MATERIAL SAFETY DATA SHEET
STATCLEAN

SECTION IV

FIRE AND EXPLOSION DATA

FLASH POINT: Not considered flammable by FHSA

FLAMMABILITY CLASSIFICATION (Aerosol): Non-Flammable

FIRE AND EXPLOSION HAZARDS: Keep away from any ignition source, i.e. open flames, welding torch or arc. At elevated temperatures (over 130°F.) containers may rupture or burst.

EXTINGUISHING MEDIA: Water Fog, CO₂, Foam, Dry Chemicals

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. Keep aerosols cooled with water and remove them from danger area as soon as possible. If aerosols are bursting, stay clear until bursting is completed. Aerosols can be projectiles when bursting.

SECTION V

REACTIVITY

STABILITY: Material is stable.

MATERIALS TO AVOID: Strong oxidizing or reducing agents.

DECOMPOSITION: May form toxic material: Carbon Dioxide, Carbon Monoxide, Various Hydrocarbons and organic compounds.

POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Open flame or any means which cause high temperatures (over 130°F.) that may cause containers to rupture or burst.

SECTION VI

HEALTH HAZARD DATA

PRINCIPLE ROUTES
OF EXPOSURE: Skin, ingestion, inhalation

CONTACT WITH EYES: Irritation

CONTACT WITH SKIN: Prolonged contact may cause irritation, defatting and dermatitis.

SKIN ABSORPTION: There may be some absorption that may cause skin irritation.

MATERIAL SAFETY DATA SHEET
STATCLEAN
SECTION VI (Cont'd)

INHALATION: Nasal and respiratory irritation.

INGESTION: Can cause gastrointestinal irritation and nausea.

CHRONIC EFFECT FROM
OVER EXPOSURE: Respiratory irritation.

PRIMARY ROUTES
OF ENTRY: Inhalation/dermal

SECTION VII

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.

SKIN: Flush skin with water. Follow by washing with soap and water. If irritation occurs get medical attention.

INHALATION: Remove to fresh air. If breathing is difficult, give oxygen and call physician. If breathing stops, begin artificial respiration; immediately seek medical attention. Keep person warm and quiet.

INGESTION: **DO NOT INDUCE VOMITING.** If vomiting occurs spontaneously, keep head below hip to prevent aspiration of liquid into lungs. Don't give anything by mouth if patient is unconscious. Get medical attention immediately.

SECTION VIII

SPILL OR LEAK PROCEDURES

SPILL, LEAK OR RELEASE: Small leaks can be mopped or wiped up immediately. Avoid breathing vapors. Large leaks should be contained using inert absorbent materials. Transfer to closed metal containers. Keep out of water supplies.

WASTE DISPOSAL: Dispose in accordance with local, state and federal regulations.

SECTION IX

SPECIAL PRECAUTIONS

SAFETY PRECAUTIONS: Keep aerosols cool in temperatures between 60 to 120°F. Do not allow temperature to rise above 120°F. May cause bursting of cans. Use non-sparking tools when handling this material. Do not weld or cut on an empty container. Keep containers dry, closed and upright when not in use. If the painted surface is to be welded, use a fan across the work area to prevent fumes from rising to the welder's face. Pump clean air into welder's hood to provide positive air pressure to prevent fumes from getting to welder. Maintain good personal hygiene and housekeeping.

MATERIAL SAFETY DATA SHEET
STATCLEAN

SECTION X

PRECAUTIONS FOR SAFE HANDLING AND USE

RESPIRATORY
PROTECTION:

Use with adequate ventilation. If TLV of products or any component is exceeded, a NIOSH/MSHA jointly approved respirator is advised in the absence of proper environmental control.

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV levels.

PROTECTIVE GLOVES:

Wear resistant rubber gloves to prevent repeated or prolonged skin contact to hands.

PROTECTIVE EQUIPMENT: Not usually required.

HYGIENIC PRACTICES:

Observe normal hygienic practices. Wash hands after use.

SECTION XI

TRANSPORT INFORMATION

PROPER SHIPPING NAME:

Transport as a consumer commodity (ORM-D) aerosol product
Consumer Commodity

HAZARD CLASS:

ORM-D

UN NUMBER:

N/A

DISCLAIMER

PERFECTDATA expressly disclaims all express or implied warranties for merchantability and fitness for a particular purpose, with respect to the product or information provided herein.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, **PERFECTDATA** makes no representations as to its accuracy or sufficiency. Conditions of use are beyond **PERFECTDATA**'s control and therefore users are responsible to verify this data under their own operation conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product, or from the publication, or use of, or reliance upon, information contained herein. This information relates only to the product designated here and does not relate to its use in combination with any other material or in any other process.